

# Vitality™ QUICK GUIDE

little **Vitality™**  
luxury™

Quick set up guide:

Follow the instructions 1 to 8.

How to replace the Vitality™ filter cartridge:  
Follow the instructions 3 to 8.

**Tip** - On the first use of the Vitality™ Filter, run the filter under running water to clear out loose carbon (this is perfectly normal).



1. In the box you will find a manual, drip tray and spare silicon O-ring for the screw cap in a plastic packet.



2. Place the drip tray into the two slots on the front of the unit.



3. Rinse the filter under a running tap / faucet, gently shaking for 60 seconds.



4. Fill the bottle with regular city / municipal tap / faucet water.



5. Tighten the screw cap onto the bottle tightly.



6. Place the filter cartridge into the filter housing.



7. Turn the bottle upside down onto the unit.



8. Note – to clean the unit pull the clip back and remove the top reservoir cover.

## Filter User Instructions

Rinse the new filter cartridge under a running tap and gently shake for 30 to 60 seconds, then soak the filter cartridge in water overnight, for optimum results soak for 24 hours before use.

1. To ensure your unit is kept clean, we recommend using dishwashing liquid every 3 months.
2. To clean the bottle, use a few drops of dishwashing liquid and half fill the bottle with lukewarm water. (DO NOT USE HOT WATER).
3. If the flow of water stalls and stops flowing freely after the filter is reinserted or replaced, remove the filter and shake the filter to loosen the carbon and then reinsert the cartridge into the dispenser. Note: DO NOT USE HOT WATER. Let the water drain and rinse with fresh water once or twice then drain through the tap and rinse the unit with fresh water.
4. When refilling the bottle with the water, it is suggested that you should tap off 1 glass of water before replacing the tap filled bottle.
5. The filters cartridges can be placed in the plastic recycle bin.

For use with municipal or city water. The contaminants or other substances removed or reduced by this water filter are not necessarily in all users' water. Do not use with water that is microbiologically unsafe, or of unknown quality, without adequate disinfection before or after the system. Systems that are certified for cyst reduction may be used on disinfected water that may contain filterable cysts. Individuals requiring water of certain microbiological purity should consult their physician. For your own health & safety use the original replacement cartridge.

**IMPORTANT**  
FOR THE Vitality™ WATER COOLER, ENSURE THE BACK OF THE UNIT IS 6" (15 CM) AWAY FROM A WALL

**CARTRIDGE REPLACEMENT GUIDE:**  
EVERY 1- 3 MONTHS MAX

1-2 PEOPLE = 2-3 MONTHS

MORE THAN 3 PEOPLE = 1-2 MONTHS